Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

FAIRCHILD SEMICONDUCTOR™

Jameco Part Number 26446

FFB2222A FMB2222A MMPQ2222A



SC70-6
Mark: .1P

NOTE: The pinouts are symmetrical; pin 1 and pin 4 are interchangeable. Units inside the carrier can be of either orientation and will not affect the functionality of the device.



SuperSOT™-6
Mark: .1P
Dot denotes pin #1



SOIC-16
Mark: MMPQ2222A

NPN Multi-Chip General Purpose Amplifier

This device is for use as a medium power amplifier and switch requiring collector currents up to 500 mA. Sourced from Process 19.

Absolute Maximum Ratings*

T_A = 25°C unless otherwise noted

Symbol	Parameter	Value	Units
V_{CEO}	Collector-Emitter Voltage	40	V
V_{CBO}	Collector-Base Voltage	75	V
V_{EBO}	Emitter-Base Voltage	5.0	V
I_C	Collector Current - Continuous	500	mA
T_J, T_{stg}	Operating and Storage Junction Temperature Range	-55 to +150	°C

*These ratings are limiting values above which the serviceability of any semiconductor device may be impaired.

NOTES:
1) These ratings are based on a maximum junction temperature of 150 degrees C.
2) These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.

Thermal Characteristics

T_A = 25°C unless otherwise noted

Symbol	Characteristic	Max			Units
		FFB2222A	FMB2222A	MMPQ2222A	
P_D	Total Device Dissipation Derate above 25°C	300 2.4	700 5.6	1,000 8.0	mW mW/°C
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient Effective 4 Die Each Die	415	180	 125 240	°C/W °C/W °C/W

© 1998 Fairchild Semiconductor Corporation

NPN Multi-Chip General Purpose Amplifier
(continued)

Electrical Characteristics
T_A = 25°C unless otherwise noted

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
OFF CHARACTERISTICS						
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage*	I_C = 10 mA, I_B = 0	40			V
$V_{(BR)CBO}$	Collector-Base Breakdown Voltage	I_C = 10 µA, I_E = 0	75			V
$V_{(BR)EBO}$	Emitter-Base Breakdown Voltage	I_E = 10 µA, I_C = 0	5.0			V
I_{CBO}	Collector Cutoff Current	V_{CB} = 60 V, I_E = 0			10	nA
I_{EBO}	Emitter Cutoff Current	V_{EB} = 3.0 V, I_C = 0			10	nA
ON CHARACTERISTICS						
h_{FE}	DC Current Gain	I_C = 0.1 mA, V_{CE} = 10 V I_C = 1.0 mA, V_{CE} = 10 V I_C = 10 mA, V_{CE} = 10 V I_C = 150 mA, V_{CE} = 10 V* I_C = 150 mA, V_{CE} = 1.0 V* I_C = 500 mA, V_{CE} = 10 V*	35 50 75 100 50 40		 300 	
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage*	I_C = 150 mA, I_B = 15 mA I_C = 500 mA, I_B = 50 mA			0.3 1.0	V V
$V_{BE(sat)}$	Base-Emitter Saturation Voltage*	I_C = 150 mA, I_B = 15 mA I_C = 500 mA, I_B = 50 mA			1.2 2.0	V V
SMALL SIGNAL CHARACTERISTICS						
f_T	Current Gain - Bandwidth Product	I_C = 20 mA, V_{CE} = 20 V, f = 100 MHz		300		MHz
C_{obo}	Output Capacitance	V_{CB} = 10 V, I_E = 0, f = 100 kHz		4.0		pF
C_{ibo}	Input Capacitance	V_{EB} = 0.5 V, I_C = 0, f = 100 kHz		20		pF
NF	Noise Figure	I_C = 100 µA, V_{CE} = 10 V, R_S = 1.0 kΩ, f = 1.0 kHz		2.0		dB
SWITCHING CHARACTERISTICS						
t_d	Delay Time	V_{CC} = 30 V, $V_{BE(OFF)}$ = 0.5 V, I_C = 150 mA, I_{B1} = 15 mA		8		ns
t_r	Rise Time			20		ns
t_s	Storage Time	V_{CC} = 30 V, I_C = 150 mA, I_{B1} = I_{B2} = 15 mA		180		ns
t_f	Fall Time			40		ns

*Pulse Test: Pulse Width ≤ 300 µs, Duty Cycle ≤ 2.0%

Spice Model

NPN (Is=14.34f Xti=3 Eg=1.11 Vaf=74.03 Bf=255.9 Ne=1.307 Ise=14.34f Ikf=.2847 Xtb=1.5 Br=6.092 Nc=2 Isc=0 Ikr=0 Rc=1 Cjc=7.306p Mjc=.3416 Vjc=.75 Fc=.5 Cje=22.01p Mje=.377 Vje=.75 Tr=46.91n Tf=411.1p Itf=.6 Vtf=1.7 Xtf=3 Rb=10)

NPN Multi-Chip General Purpose Amplifier
(continued)

Typical Characteristics

Typical Pulsed Current Gain vs Collector Current



Collector-Emitter Saturation Voltage vs Collector Current



Base-Emitter Saturation Voltage vs Collector Current



Base-Emitter ON Voltage vs Collector Current



Collector-Cutoff Current vs Ambient Temperature



Emitter Transition and Output Capacitance vs Reverse Bias Voltage



Typical Characteristics (continued)

Turn On and Turn Off Times vs Collector Current



Switching Times vs Collector Current



Power Dissipation vs Ambient Temperature



NPN Multi-Chip General Purpose Amplifier
(continued)

Typical Common Emitter Characteristics (f = 1.0kHz)







Test Circuits



FIGURE 1: Saturated Turn-On Switching Time



FIGURE 2: Saturated Turn-Off Switching Time

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEx™
Bottomless™
CoolFET™
CROSSVOLT™
DOME™
E^2CMOS^{TM}
EnSigna™
FACT™
FACT Quiet Series™
FAST®
FASTr™
GlobalOptoisolator™
GTO™
HiSeC™
ISOPLANAR™
MICROWIRE™
OPTOLOGIC™
OPTOPLANAR™
PACMAN™
POP™
PowerTrench®
QFET™
QS™
QT Optoelectronics™
Quiet Series™
SILENT SWITCHER®
SMART START™
SuperSOT™-3
SuperSOT™-6
SuperSOT™-8
SyncFET™
TinyLogic™
UHC™
VCX™

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.
As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.